



Specification Comparison Summary	Series 860	Series 600	Series 860 vs. Series 600
Status	<u>New</u>	<u>obsolete</u>	
Pressure Range	choose from: 0.25"WC to 40 PSI (custom & bi-directional ranges available)	Choose from: 1"WC to 150 PSI (custom & bi-directional ranges available)	860 Better (Has lower ranges available)
Stability	Less than +/-0.5% F.S.O./yr.	Less than +/-2% F.S.O./yr.	860 Better
Overpressure	20 PSI or 2X FSP, whichever is greater	14.5PSI or 2X Full Scale Pressure, whichever is greater	860 Better
Media	Limited only to media that will not attack Polyphenylene Sulfide (PPS), polyetherimide (PEI), silicon, or fluorosilicone, silicone RTV. Note that liquids are allowed in either or both ports.	Any Dry Air or inert non-conductive gas	860 Better
Adjustments	Offset 60% of F.S.O. minimum	Offset (10% of FSO)	860 Better
Electrical Connections	Pluggable Screw Terminal Block	22 AWG 3-conductor cable	860 Better
Dimensions	Approx. 3.5" x 2.7" x 1.4" (8.7cm x 6.8cm x 3.5cm) with mounting flanges	Approx. 2.25" x 0.72" x 2.5" (5.72cm x 1.83cm x 6.35cm)	860 Slightly Bigger